

Drainage Impact Assessment

Proposed Aldi Store Portobello Road Edinburgh

For

Aldi Stores Limited



Contents

1.00 Introduction

2.00 Site Location and Topography

3.00 Flood Risk

4.00 Surface Water Run Off

5.00 Foul Drainage

6.00 Summary and Recommendations

Appendix A Location Plan

Appendix B Topographical Survey

Appendix C Proposed Development Plan

Appendix D Proposed Drainage Layout Plan

Appendix E Calculations

Report ref	Issue	Prepared by	Date	Reviewed by	Date
14517	1	M.Pearse	Feb 2015	A.Wallace	Feb 2015



1.0 Introduction

- 1.01 This report is commissioned by Aldi Stores Limited to examine the drainage impact associated with the proposed redevelopment of land at Portobello Road, Edinburgh. This Assessment is reviewed in accordance with the current Scottish planning Policy (SPP).
- 1.02 This phase of the development site occupies a total area of approximately 0.7 hectares and currently falls in a northerly towards Portobello Road.
- 1.03 Aldi Stores Limited plans to redevelop this phase of the site to provide a new store and associated car parking and delivery areas. A new access road off Portobello Road will be provided.
- 1.04 This report is based on information received from Scottish Water together with a review of the online SEPA flood maps. A Phase 2 Geo Environmental Assessment has been undertaken by 3e Consulting Engineers. A Flood Risk Assessment and Drainage Impact Assessment was undertaken by WSP Group for the whole development area.
- 1.05 Section 2.00 of this report describes the site location and topography. Section 3.00 identifies the flood risks. Section 4.00 discusses the surface water drainage. Section 5.00 discusses the foul water drainage. Section 6.00 provides conclusions and recommendations.

2.0 Site Location and Topography

- 2.01 The site is centred at National Grid Reference 330130, 674220 and is located to the northern end of Portobello approximately 4.25km east of Edinburgh City Centre.
- 2.02 The site is currently occupied by a former fuel filling station, areas of car parking used for vehicle sales and a building occupied by mixed commercial businesses.
- 2.03 Existing ground levels fall in a northerly direction from the southern boundary, from a level of around 12.00mAOD, down to 10.40mAOD at the back of the footway on Portobello Road at the northern boundary.
- 2.04 Portobello High Street to the north falls in an easterly direction from 10.85mAOD to the west of the new access down to 10.00m to the east of the site.
- 2.05 The land to the east and south of the site rises with a fall towards to the site boundary.
- 2.06 The Figgate Burn is located approximately 95m east of the site and is culverted under Portobello High Street. The Figgate Burn is then an open watercourse where it then discharges into the Firth of Forth 250m to the north.
- 2.07 Aldi Stores Limited plans to redevelop the site to provide a new store, associated car parking and delivery areas. A site access will be provided which will be used to serve the proposed housing development to the south of the site area of the site.



- 2.08 Levels will be reduced across the site to provide the gradients required by Aldi Stores Ltd. This will result in batters/retaining being required along the southern and eastern boundaries.
- 2.09 See Appendix C for a copy of the Proposed Development Plan.

3.0 Flood Risk

- 3.01 As required by Scottish Planning Policy, all potential sources of flooding need to be considered; Rivers, Sea, Land, Groundwater, Sewers and Artificial Sources i.e. reservoirs and canals.
- 3.02 A Flood Risk assessment has been undertaken by WSP Group for the whole development site. This confirmed that the SEPA flood maps do not show any signs of fluvial flooding which may affect the development.
- 3.03 They also confirmed the 1 in 200 year flood level at the Figgate Burn to the East of the site is 6.02mAOD. This flood level is approximately 4m below the proposed site levels. As such the site is at low risk of fluvial flooding.
- 3.04 A 300mm diameter public combined sewer is located within Portobello High Street to the north which flows in an easterly direction away from the site. Surface water from the existing hard standings and buildings are shown to currently discharge into this combined sewer.
- 3.05 It is proposed for surface water flows from the development to be directed to Figgate Burn via the public surface water sewer to the east of the site. This will remove the surface water from this combined sewer for the area being developed. This will reduce the risk of flooding from the combined sewer. Should any flooding occur within Portobello High Street due to blockage it is considered that flood water would flow in an easterly direction away from the development.
- 3.06 Overland flows will need to be considered from the land to the south and east of the site as the development in these areas will be at a higher elevation in relation to the site. A cut off drain will be required along these boundaries to reduce any risk of overland flows from these future areas of development.

Drainage Impact

4.0 Surface Water Run Off

- 4.01 The existing site is currently classed as a brownfield development. A Drainage Impact Assessment for the residential and Aldi development was undertaken by WSP Group as part of the original planning application.
- 4.02 WSP Group consulted Scottish Water as part of this process and they confirmed that surface water flows from the site should discharge to the 300mm diameter surface water sewer in Portobello High Street to the east of the site.

- 4.03 Further to discussions with the Edinburgh City Council Flood Prevention Officers any discharge to the surface water sewer will need to be restricted to a greenfield run off rate due to this sewer ultimately discharging into the Figgate Burn.
- 4.04 Surface water flows are to be restricted to a maximum flow of 4.5 l/s/hectare. This will result in a maximum discharge from the Aldi development of 2.5 l/s. (Based on an impermeable area of 0.55 hectares). The overall development will have a total restriction of approximately 12 l/s prior to connection into the public surface water sewer. (This will be subject to the final confirmation of impermeable areas for the remainder of the site.)
- 4.05 Surface water attenuation will be required within the Aldi site. This will be provided by a mixture of porous paving with storage within the sub base and within a cellular storage tank located under the car park.
- 4.06 The surface water storage volumes have been designed to accommodate a 1 in 200 year storm event with no flooding to the site as required by Edinburgh City Council Flood Prevention Team.
- 4.07 In line with Scottish Planning Policy, the implementation of SUDS to restrict flows and improve water quality will be utilised on this scheme. Surface water run-off from the car park should receive two levels of treatment prior to discharge to the drainage network. This will be done with the use of porous car parking and granular stone sub base under the parking bays.
- 4.08 The attenuation required on the site to accommodate a 1 in 100 year storm event is in the order of 260m3. The storage required to accommodate the 1 in 200 year storm event is 310m3. This is to be provided within the proposed drainage system, the stone sub base of the parking bays and within an online cellular storage tanks under the car park.
- 4.09 Storm events in excess of the 1 in 200 year event will be stored at surface within the car park until such time as water will exit the front of the site into Portobello High Street with no flooding to the proposed store.
- 4.10 It is proposed for the outfall sewer from the site to be adopted by Scottish Water
- 4.11 A copy of the preliminary drainage layout is shown in Appendix D.
- 4.12 Copies of the surface water calculations are included in Appendix E.

5.0 Foul Drainage

- 5.01 A 300mm combined sewer is located in Portobello Road to the north of the site. This sewer is approximately 1m in depth.
- 5.02 Foul water flows from the site are proposed to discharge to the public sewer with a disconnection manhole constructed at the site boundary. It is proposed for the service ramp area to discharge to the public combined sewer. This will need to be pumped upto the gravity outfall due to the levels of the combined sewer.


- 5.03 Scottish Water have confirmed to WSP Group, as part of the drainage strategy for the whole of the site, that foul water flows can discharge to the public combined sewer adjacent to the site.
- 5.04 The above is subject to a new connection application been submitted to Scottish Water which will be progressed as part of the detailed design.
- 5.05 A copy of the drainage layout is shown in Appendix C.

6.0 Summary and Recommendations

- 6.01 The risk of flooding to the development site can be deemed as low having considered all potential sources.
- 6.02 The proposed development will not exacerbate flooding elsewhere.
- 6.03 The use of infiltration techniques has been discounted due to the potential ground conditions.
- 6.04 Surface water flows are to be directed to the existing 300mm diameter public surface water sewer to the east of the site which ultimately discharges into the Figgate Burn.
- 6.05 Surface water flows from the Aldi site will be restricted to 2.5 litres per second with attenuation been provided on the site to accommodate storms upto the 1 in 200 year event in line with Edinburgh City Council requirements
- 6.06 Surface water run-off from the car park will receive two levels of treatment with the use of porous paving and granular stone sub base.
- 6.07 Foul water flows are to discharge to the existing public combined sewer located in Portobello Road.




Appendix A
Location Plan





Appendix B Topographical Survey






Appendix C
Proposed Development
Plan





Appendix D
Proposed Drainage
Layout Plan





Appendix E
Calculations

3e Consulting Engineers				
1st Floor Block C	Aldi - Portobello Road			
Holland Park		4		
Newcastle Upon Tyne NE2 4LD		Micco		
Date Feb 2015	Designed by M. Pearse	Desipago		
File PORTOBELLO.MDX	Checked by	niailiade		
Micro Drainage	Network 2014.1.1			

STORM SEWER DESIGN by the Modified Rational Method

Design Criteria for Storm

Pipe Sizes STANDARD Manhole Sizes STANDARD

FSR Rainfall Model - Scotland and Ireland

Return Period (years) 2 Add Flow / Climate Change (%) 0 M5-60 (mm) 12.500 Minimum Backdrop Height (m) 0.000 Ratio R 0.250 Maximum Backdrop Height (m) 0.000 Maximum Rainfall (mm/hr) 100 Min Design Depth for Optimisation (m) 1.200 Maximum Time of Concentration (mins) 30 Min Vel for Auto Design only (m/s) 1.00 Foul Sewage (l/s/ha) 0.000 Min Slope for Optimisation (1:X) 500 Volumetric Runoff Coeff. 0.750

Designed with Level Soffits

Time Area Diagram for Storm

Time Area Time Area (mins) (ha) (mins) (ha) 0-4 0.160 4-8 0.483

Total Area Contributing (ha) = 0.643

Total Pipe Volume $(m^3) = 10.329$

Network Design Table for Storm

« - Indicates pipe capacity < flow

PN	Length	Fall	Slope	I.Area	T.E.	Ba	ase	k	HYD	DIA	Auto
	(m)	(m)	(1:X)	(ha)	(mins)	Flow	(1/s)	(mm)	SECT	(mm)	Design
1.000	49.000	0.327	149.8	0.023	3.00		0.0	0.600	0	150	ð
1.001	30.000	0.500	60.0	0.028	0.00		0.0	0.600	0	150	₩
1.002	4.000	0.040	100.0	0.000	0.00		0.0	0.600	0	150	ď
2.000	30.000	0.200	150.0	0.054	3.00		0.0	0.600	0	150	&

Network Results Table

PN	Rain	T.C.	US/IL	Σ I.Area	Σ Base	Foul	Add Flow	Vel	Cap	Flow
	(mm/hr)	(mins)	(m)	(ha)	Flow $(1/s)$	(l/s)	(1/s)	(m/s)	(1/s)	(1/s)
1.000	38.57	4.00	9.760	0.023	0.0	0.0	0.0	0.82	14.5	2.4
1.001	37.44	4.38	9.433	0.051	0.0	0.0	0.0	1.30	23.0	5.2
1.002	37.25	4.45	8.933	0.051	0.0	0.0	0.0	1.00	17.8	5.2
2.000	39.81	3.61	9.430	0.054	0.0	0.0	0.0	0.82	14.5	5.8

©1982-2014 XP Solutions

3e Consulting Engineers		Page 2
1st Floor Block C	Aldi - Portobello Road	
Holland Park		
Newcastle Upon Tyne NE2 4LD		Micro
Date Feb 2015	Designed by M. Pearse	Drainage
File PORTOBELLO.MDX	Checked by	Dialilade
Micro Drainage	Network 2014.1.1	

Network Design Table for Storm

PN	Length	Fall	Slope	<pre>I.Area</pre>	T.E.	Base	k	HYD	DIA	Auto
	(m)	(m)	(1:X)	(ha)	(mins)	Flow (1/s)	(mm)	SECT	(mm)	Design
3.000	40.000	0.267	149.8	0.053	3.00	0.0	0.600	0	150	ď
										_
4.000	40.000	0.267	149.8	0.023	3.00	0.0	0.600	0	150	ð
5.000	37.000	0.740	50.0	0.063	3.00	0.0	0.600	0	150	ð
5.001	40.000	0.267	149.8	0.079	0.00	0.0	0.600	0	225	ď
	14.000			0.170	0.00		0.600	0	225	8
3.002	11.000	0.000	130.3	0.170	0.00	0.0	0.000	Ü	223	•
1.003	3 000	0.020	150 0	0.000	0.00	0 0	0.600	0	300	₫
	11.000			0.000	0.00		0.600			u u
1.004	11.000	0.073	150.7	0.000	0.00	0.0	0.600	0	150	•
6 000	20 000	0 000	150 0	0 075	2 00	0.0	0 600		1.50	
6.000	30.000			0.075	3.00		0.600	0	150	ď
6.001	35.000	0.233	150.2	0.056	0.00	0.0	0.600	0	150	ď
6.002	48.000	0.320	150.0	0.019	0.00	0.0	0.600	0	150	₫*
										_
1.005	22.000	0.147	149.7	0.000	0.00	0.0	0.600	0	150	•
1.006	75.000	0.500	150.0	0.000	0.00	0.0	0.600	0	150	ē
										-

Network Results Table

PN	Rain	T.C.	US/IL	Σ I.Area	Σ Base	Foul	Add Flow	Vel	Cap	Flow
	(mm/hr)	(mins)	(m)	(ha)	Flow (1/s)	(l/s)	(1/s)	(m/s)	(1/s)	(1/s)
3.000	39.15	3.81	9.200	0.053	0.0	0.0	0.0	0.82	14.5	5.6
4.000	39.15	3.81	9.170	0.023	0.0	0.0	0.0	0.82	14.5	2.4
5.000	40.42	3.43	9.620	0.063	0.0	0.0	0.0	1.43	25.2	6.9
5.001	38.39	4.06	8.805	0.142	0.0	0.0	0.0	1.07	42.4	14.8
5.002	37.74	4.28	8.538	0.312	0.0	0.0	0.0	1.06	42.3	31.9
1.003	37.14	4.49	8.370	0.493	0.0	0.0	0.0	1.28	90.6	49.6
1.004	36.53	4.71	8.350	0.493	0.0	0.0	0.0	0.82	14.4«	49.6
6.000	39.81	3.61	9.700	0.075	0.0	0.0	0.0	0.82	14.5	8.1
6.001	37.60	4.32	9.500	0.131	0.0	0.0	0.0	0.82	14.4	13.3
6.002	35.03	5.30	9.267	0.150	0.0	0.0	0.0	0.82	14.5	14.2
1.005	34.00	5.75	8.277	0.643	0.0	0.0	0.0	0.82	14.5«	59.2
1.006	30.99	7.28	8.130	0.643	0.0	0.0	0.0	0.82	14.5«	59.2

Free Flowing Outfall Details for Storm

Outfall Outfall C. Level I. Level Min D,L W

Pipe Number Name (m) (m) I. Level (mm) (mm)

(m) 1.006 2112 9.700 7.630 0.000 1200 0

©1982-2014 XP Solutions

3e Consulting Engineers					
1st Floor Block C	Aldi - Portobello Road				
Holland Park		4			
Newcastle Upon Tyne NE2 4LD		Micco			
Date Feb 2015	Designed by M. Pearse	Drainane			
File PORTOBELLO.MDX	Checked by	niailiade			
Micro Drainage	Network 2014.1.1				

Online Controls for Storm

Crown Vortex Valve® Manhole: 6, DS/PN: 1.004, Volume (m³): 2.4

Design Head (m) 1.650 Vortex Valve® Type R1 SW Only Invert Level (m) 8.350 Design Flow (1/s) $\,$ 2.5 Diameter (mm) $\,$ 57

Depth (m)	Flow (1/s)	Depth (m) I	Flow (1/s)	Depth (m) Flo	ow (1/s)	Depth (m)	Flow (1/s)
0.100	0.7	1.200	2.1	3.000	3.3	7.000	5.1
0.200	0.9	1.400	2.3	3.500	3.6	7.500	5.3
0.300	1.1	1.600	2.4	4.000	3.8	8.000	5.4
0.400	1.2	1.800	2.6	4.500	4.1	8.500	5.6
0.500	1.4	2.000	2.7	5.000	4.3	9.000	5.8
0.600	1.5	2.200	2.9	5.500	4.5	9.500	5.9
0.800	1.7	2.400	3.0	6.000	4.7		
1.000	1.9	2.600	3.1	6.500	4.9		

Crown Vortex Valve® Manhole: 2, DS/PN: 1.005, Volume (m^3) : 4.7

Design Head (m) 1.800 Vortex Valve® Type R3 SW Only Invert Level (m) 8.277 Design Flow (1/s) 12.8 Diameter (mm) 94

Depth (m) Fl	ow (1/s)	Depth (m)	Flow (1/s)	Depth (m) Fl	low (1/s)	Depth (m)	Flow (1/s)
0.100	2.7	1.200	10.4	3.000	16.5	7.000	25.2
0.200	4.3	1.400	11.3	3.500	17.8	7.500	26.1
0.300	5.2	1.600	12.1	4.000	19.1	8.000	27.0
0.400	6.0	1.800	12.8	4.500	20.2	8.500	27.8
0.500	6.7	2.000	13.5	5.000	21.3	9.000	28.6
0.600	7.4	2.200	14.1	5.500	22.3	9.500	29.4
0.800	8.5	2.400	14.8	6.000	23.3		
1.000	9.5	2.600	15.4	6.500	24.3		

3e Consulting Engineers	Page 4	
1st Floor Block C	Aldi - Portobello Road	
Holland Park		4
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Desipage
File PORTOBELLO.MDX	Checked by	Drainage
Micro Drainage	Network 2014.1.1	'

Storage Structures for Storm

Porous Car Park Manhole: 11, DS/PN: 1.001

Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	5.0
Membrane Percolation (mm/hr)	1000	Length (m)	46.0
Max Percolation (1/s)	63.9	Slope (1:X)	200.0
Safety Factor	2.0	Depression Storage (mm)	5
Porosity	0.30	Evaporation (mm/day)	3
<pre>Invert Level (m)</pre>	10.170	Cap Volume Depth (m)	0.450

Porous Car Park Manhole: 10, DS/PN: 1.002

Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	5.0
Membrane Percolation (mm/hr)	1000	Length (m)	39.0
Max Percolation (1/s)	54.2	Slope (1:X)	90.0
Safety Factor	2.0	Depression Storage (mm)	5
Porosity	0.30	Evaporation (mm/day)	3
Invert Level (m)	9.540	Cap Volume Depth (m)	0.600

Porous Car Park Manhole: RE2, DS/PN: 2.000

Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	5.0
Membrane Percolation (mm/hr)	1000	Length (m)	38.0
Max Percolation (1/s)	52.8	Slope (1:X)	200.0
Safety Factor	2.0	Depression Storage (mm)	5
Porosity	0.30	Evaporation (mm/day)	3
Invert Level (m)	9.945	Cap Volume Depth (m)	0.450

Porous Car Park Manhole: RE3, DS/PN: 3.000

Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	5.0
Membrane Percolation (mm/hr)	1000	Length (m)	38.0
Max Percolation (1/s)	52.8	Slope (1:X)	200.0
Safety Factor	2.0	Depression Storage (mm)	5
Porosity	0.30	Evaporation (mm/day)	3
<pre>Invert Level (m)</pre>	9.700	Cap Volume Depth (m)	0.600

Porous Car Park Manhole: RE4, DS/PN: 4.000

Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	5.0
Membrane Percolation (mm/hr)	1000	Length (m)	38.0
Max Percolation (1/s)	52.8	Slope (1:X)	200.0
Safety Factor	2.0	Depression Storage (mm)	5
Porosity	0.30	Evaporation (mm/day)	3
Invert Level (m)	9.650	Cap Volume Depth (m)	0.600

Porous Car Park Manhole: 9, DS/PN: 5.001

Infiltration	Coefficient	Base	(m/hr)	0.00000	Max	Percolation (1/s)	48.6
Membi	ane Percola	tion ((mm/hr)	1000		Safety Factor	2.0

3e Consulting Engineers		Page 5
1st Floor Block C	Aldi - Portobello Road	
Holland Park		
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Drainage
File PORTOBELLO.MDX	Checked by	Diamade
Micro Drainage	Network 2014.1.1	

Porous Car Park Manhole: 9, DS/PN: 5.001

Porosity 0.30 Slope (1:X) 50.0

Invert Level (m) 9.703 Depression Storage (mm) 5

Width (m) 5.0 Evaporation (mm/day) 3

Length (m) 35.0 Cap Volume Depth (m) 0.450

Porous Car Park Manhole: 8, DS/PN: 5.002

Infiltration Coefficient Base (m/hr) 0.00000 Width (m) 5.0 Membrane Percolation (mm/hr) 1000 Length (m) 29.0 Max Percolation (l/s) 40.3 Slope (l:X) 200.0 Safety Factor 2.0 Depression Storage (mm) 5 Porosity 0.30 Evaporation (mm/day) 3 Invert Level (m) 9.420 Cap Volume Depth (m) 0.600

Cellular Storage Manhole: 7, DS/PN: 1.003

Invert Level (m) 8.370 Safety Factor 2.0 Infiltration Coefficient Base (m/hr) 0.00000 Porosity 0.95 Infiltration Coefficient Side (m/hr) 0.00000

Depth (m) Area (m²) Inf. Area (m²) Depth (m) Area (m²) Inf. Area (m²)

0.000 100.0 0.0 0.0 0.801 0.0 0.0

0.800 100.0 0.0

3e Consulting Engineers		Page 6
1st Floor Block C	Aldi - Portobello Road	
Holland Park		
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Drainage
File PORTOBELLO.MDX	Checked by	Dialilade
Micro Drainage	Network 2014.1.1	

30 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000 Hot Start (mins) 0 MADD Factor * $10m^3$ /ha Storage 2.000 Hot Start Level (mm) 0 Inlet Coefficient 0.800 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (1/per/day) 0.000 Foul Sewage per hectare (1/s) 0.000

Number of Input Hydrographs 0 Number of Storage Structures 8 Number of Online Controls 2 Number of Time/Area Diagrams 0 Number of Offline Controls 0 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR Ratio R 0.250 Region Scotland and Ireland Cv (Summer) 0.750 M5-60 (mm) 12.400 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm) 300.0

Analysis Timestep 2.5 Second Increment (Extended)

DTS Status

ON

DVD Status

ON

Inertia Status

Profile(s) Summer and Winter
Duration(s) (mins) 15, 30, 60, 120, 180, 240, 360, 480, 600,
720, 960, 1440, 2160, 2880, 4320

Return Period(s) (years) 30, 100, 200
Climate Change (%) 0, 0, 0

			Return	Climate	Firs	First X		First Z	O/F	Lvl
PN	St	torm	Period	Change	Surch	arge	Flood	Overflow	Act.	Exc.
1.000	1440	Winter	30	0%	100/240	Winter				
1.001	1440	Winter	30	0%	30/180	Winter				
1.002	1440	Winter	30	0%	30/120	Summer				
2.000	1440	Winter	30	0%	30/180	Winter				
3.000	1440	Winter	30	0%	30/120	Winter				
4.000	1440	Winter	30	0%	30/120	Winter				
5.000	960	Winter	30	0%	30/360	Winter				
5.001	1440	Winter	30	0%	30/60	Winter				
5.002	1440	Winter	30	0%	30/15	Summer				
1.003	1440	Winter	30	0%	30/15	Summer				
1.004	1440	Winter	30	0%	30/15	Summer				
6.000	15	Winter	30	0%	30/15	Summer				
6.001	15	Winter	30	0%	30/15	Summer				
6.002	30	Winter	30	0%	30/15	Summer				
1.005	30	Winter	30	0%	30/15	Summer				
1.006	30	Winter	30	0%						

3e Consulting Engineers		Page 7
1st Floor Block C	Aldi - Portobello Road	
Holland Park		4
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Desinado
File PORTOBELLO.MDX	Checked by	Diamage
Micro Drainage	Network 2014.1.1	

$\frac{\text{30 year Return Period Summary of Critical Results by Maximum Level (Rank 1)}}{\text{for Storm}}$

		Water		Flooded			Pipe	
	US/MH	Level	Surch'ed	Volume	Flow /	O'flow	Flow	
PN	Name	(m)	Depth (m)	(m³)	Cap.	(1/s)	(l/s)	Status
1.000	RE1	9.855	-0.055	0.000	0.02	0.0	0.3	OK
1.001	11	9.855	0.272	0.000	0.03	0.0	0.7	SURCHARGED
1.002	10	9.855	0.772	0.000	0.12	0.0	1.4	SURCHARGED
2.000	RE2	9.881	0.301	0.000	0.06	0.0	0.8	SURCHARGED
3.000	RE3	9.851	0.501	0.000	0.05	0.0	0.8	SURCHARGED
4.000	RE4	9.849	0.529	0.000	0.03	0.0	0.5	SURCHARGED
5.000	RE	9.866	0.096	0.000	0.05	0.0	1.2	SURCHARGED
5.001	9	9.864	0.834	0.000	0.05	0.0	1.9	SURCHARGED
5.002	8	9.865	1.102	0.000	0.11	0.0	4.1	SURCHARGED
1.003	7	9.941	1.271	0.000	0.11	0.0	5.5	SURCHARGED
1.004	6	9.963	1.463	0.000	0.18	0.0	2.3	SURCHARGED
6.000	5	10.057	0.207	0.000	0.85	0.0	11.8	SURCHARGED
6.001	4	9.969	0.319	0.000	1.25	0.0	17.5	SURCHARGED
6.002	3	9.750	0.333	0.000	1.08	0.0	15.2	SURCHARGED
1.005	2	9.530	1.103	0.000	0.77	0.0	10.5	SURCHARGED
1.006	1	8.226	-0.054	0.000	0.73	0.0	10.4	OK

3e Consulting Engineers		Page 8
1st Floor Block C	Aldi - Portobello Road	
Holland Park		
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Drainane
File PORTOBELLO.MDX	Checked by	namaye
Micro Drainage	Network 2014.1.1	

100 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000 Hot Start (mins) 0 MADD Factor * $10m^3$ /ha Storage 2.000 Hot Start Level (mm) 0 Inlet Coefficient 0.800 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (1/per/day) 0.000 Foul Sewage per hectare (1/s) 0.000

Number of Input Hydrographs 0 Number of Storage Structures 8 Number of Online Controls 2 Number of Time/Area Diagrams 0 Number of Offline Controls 0 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR Ratio R 0.250 Region Scotland and Ireland Cv (Summer) 0.750 M5-60 (mm) 12.400 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm) 300.0

Analysis Timestep 2.5 Second Increment (Extended)

DTS Status

ON

DVD Status

ON

Inertia Status

Profile(s) Summer and Winter
Duration(s) (mins) 15, 30, 60, 120, 180, 240, 360, 480, 600,
720, 960, 1440, 2160, 2880, 4320

Return Period(s) (years) 30, 100, 200
Climate Change (%) 0, 0, 0

			Return	Climate	First X		First Y	First Z	O/F	Lvl
PN	Sto	orm	Period	Change	Surch	arge	Flood	Overflow	Act.	Exc.
1.000	1440 T	Winter	100	0%	100/240	Winter				
1.001	1440 T	Winter	100	0%	30/180	Winter				
1.002	1440 T	Winter	100	0%	30/120	Summer				
2.000	1440 1	Winter	100	0%	30/180	Winter				
3.000	1440 1	Winter	100	0%	30/120	Winter				
4.000	1440 1	Winter	100	0%	30/120	Winter				
5.000	1440 1	Winter	100	0%	30/360	Winter				
5.001	1440 1	Winter	100	0%	30/60	Winter				
5.002	1440 1	Winter	100	0%	30/15	Summer				
1.003	1440 1	Winter	100	0%	30/15	Summer				
1.004	1440 1	Winter	100	0%	30/15	Summer				
6.000	30 1	Winter	100	0%	30/15	Summer				
6.001	30 1	Winter	100	0%	30/15	Summer				
6.002	30 1	Winter	100	0%	30/15	Summer				
1.005	30 1	Winter	100	0%	30/15	Summer				
1.006	30 1	Winter	100	0%						

3e Consulting Engineers		Page 9
1st Floor Block C	Aldi - Portobello Road	
Holland Park		
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Drainage
File PORTOBELLO.MDX	Checked by	namaye
Micro Drainage	Network 2014.1.1	

$\frac{\text{100 year Return Period Summary of Critical Results by Maximum Level (Rank}}{\text{1) for Storm}}$

		Water		${\tt Flooded}$			Pipe	
	US/MH	Level	Surch'ed	Volume	Flow /	O'flow	Flow	
PN	Name	(m)	Depth (m)	(m³)	Cap.	(1/s)	(l/s)	Status
1.000	RE1	10.030	0.120	0.000	0.03	0.0	0.4	SURCHARGED
1.001	11	10.030	0.447	0.000	0.04	0.0	0.9	SURCHARGED
1.002	10	10.029	0.946	0.000	0.12	0.0	1.4	FLOOD RISK
2.000	RE2	10.028	0.448	0.000	0.08	0.0	1.1	SURCHARGED
3.000	RE3	10.026	0.676	0.000	0.07	0.0	0.9	SURCHARGED
4.000	RE4	10.024	0.704	0.000	0.05	0.0	0.7	SURCHARGED
5.000	RE	10.042	0.272	0.000	0.05	0.0	1.1	SURCHARGED
5.001	9	10.040	1.010	0.000	0.05	0.0	2.2	FLOOD RISK
5.002	8	10.041	1.278	0.000	0.13	0.0	4.8	FLOOD RISK
1.003	7	10.121	1.451	0.000	0.11	0.0	5.4	FLOOD RISK
1.004	6	10.142	1.642	0.000	0.19	0.0	2.5	FLOOD RISK
6.000	5	10.396	0.546	0.000	0.78	0.0	10.9	SURCHARGED
6.001	4	10.346	0.696	0.000	1.24	0.0	17.2	SURCHARGED
6.002	3	10.167	0.750	0.000	1.23	0.0	17.3	SURCHARGED
1.005	2	9.879	1.452	0.000	0.86	0.0	11.8	SURCHARGED
1.006	1	8.235	-0.045	0.000	0.82	0.0	11.7	OK

3e Consulting Engineers		Page 10
1st Floor Block C	Aldi - Portobello Road	
Holland Park		
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Drainage
File PORTOBELLO.MDX	Checked by	Dialilade
Micro Drainage	Network 2014.1.1	

200 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000 Hot Start (mins) 0 MADD Factor * $10m^3$ /ha Storage 2.000 Hot Start Level (mm) 0 Inlet Coefficient 0.800 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (1/per/day) 0.000 Foul Sewage per hectare (1/s) 0.000

Number of Input Hydrographs 0 Number of Storage Structures 8 Number of Online Controls 2 Number of Time/Area Diagrams 0 Number of Offline Controls 0 Number of Real Time Controls 0

Synthetic Rainfall Details

Rainfall Model FSR Ratio R 0.250 Region Scotland and Ireland Cv (Summer) 0.750 M5-60 (mm) 12.400 Cv (Winter) 0.840

Margin for Flood Risk Warning (mm) 300.0

Analysis Timestep 2.5 Second Increment (Extended)

DTS Status

ON

DVD Status

ON

Inertia Status

Profile(s) Summer and Winter
Duration(s) (mins) 15, 30, 60, 120, 180, 240, 360, 480, 600,
720, 960, 1440, 2160, 2880, 4320

Return Period(s) (years) 30, 100, 200
Climate Change (%) 0, 0, 0

			Return	Climate	First X		First Y	First Z	O/F	Lvl
PN	Storm Period Change		Surch	arge	Flood	Overflow	Act.	Exc.		
1.000	1440	Winter	200	0%	100/240	Winter				
1.001	1440	Winter	200	0%	30/180	Winter				
1.002	1440	Winter	200	0%	30/120	Summer				
2.000	1440	Winter	200	0%	30/180	Winter				
3.000	1440	Winter	200	0%	30/120	Winter				
4.000	1440	Winter	200	0%	30/120	Winter				
5.000	1440	Winter	200	0%	30/360	Winter				
5.001	1440	Winter	200	0%	30/60	Winter				
5.002	1440	Winter	200	0%	30/15	Summer				
1.003	1440	Winter	200	0%	30/15	Summer				
1.004	1440	Winter	200	0%	30/15	Summer				
6.000	30	Winter	200	0%	30/15	Summer				
6.001	30	Winter	200	0%	30/15	Summer				
6.002	30	Winter	200	0%	30/15	Summer				
1.005	30	Winter	200	0%	30/15	Summer				
1.006	30	Winter	200	0%						

3e Consulting Engineers	Page 11	
1st Floor Block C	Aldi - Portobello Road	
Holland Park		
Newcastle Upon Tyne NE2 4LD		Micco
Date Feb 2015	Designed by M. Pearse	Desinado
File PORTOBELLO.MDX	Checked by	Dialilade
Micro Drainage	Network 2014.1.1	

$\frac{\text{200 year Return Period Summary of Critical Results by Maximum Level (Rank }}{\text{1) for Storm}}$

	Water			${\tt Flooded}$		Pipe		
	US/MH	Level	Surch'ed	Volume	Flow /	O'flow	Flow	
PN	Name	(m)	Depth (m)	(m³)	Cap.	(1/s)	(l/s)	Status
1.000	RE1	10.142	0.232	0.000	0.03	0.0	0.5	SURCHARGED
1.001	11	10.142	0.559	0.000	0.04	0.0	0.9	SURCHARGED
1.002	10	10.141	1.058	0.000	0.12	0.0	1.5	FLOOD RISK
2.000	RE2	10.139	0.559	0.000	0.09	0.0	1.2	SURCHARGED
3.000	RE3	10.139	0.789	0.000	0.07	0.0	1.0	SURCHARGED
4.000	RE4	10.137	0.817	0.000	0.05	0.0	0.7	SURCHARGED
5.000	RE	10.151	0.381	0.000	0.05	0.0	1.2	SURCHARGED
5.001	9	10.149	1.119	0.000	0.06	0.0	2.3	FLOOD RISK
5.002	8	10.173	1.410	0.000	0.13	0.0	5.0	FLOOD RISK
1.003	7	10.227	1.557	0.000	0.10	0.0	5.1	FLOOD RISK
1.004	6	10.248	1.748	0.000	0.20	0.0	2.5	FLOOD RISK
6.000	5	10.733	0.883	0.000	0.80	0.0	11.1	SURCHARGED
6.001	4	10.676	1.026	0.000	1.30	0.0	18.1	SURCHARGED
6.002	3	10.463	1.046	0.000	1.31	0.0	18.5	SURCHARGED
1.005	2	10.125	1.698	0.000	0.93	0.0	12.7	FLOOD RISK
1.006	1	8.240	-0.040	0.000	0.88	0.0	12.6	OK